

Barricade

Your property and access, our challenge

VERTICAL BAR FENCING



Barricade: functional and timeless

With the Barricade chain link fencing B&G has a functional and timeless classic in its range. The sleek and modern looking fence is applicable on a wide variety of sites. Characteristic are the round bars which are placed between the beams. Also striking is the dragon tail.

We apply it standard on the Barricade fencing of 1.5 meter and up as anti-climb protection.

Firmly anchored

In order to firmly anchor the Barricade fencing for years, B&G drives the posts deep into the soil. The blind connections between posts and bar panels

further promote safety. They are vandal-resistant and prevent unwanted disassembly.

Application

Barricade vertical bar fencing is very suitable for sites where sleek, sustainable fencing is desired. We often apply it around:

- business parks
- industrial sites
- schools
- sports grounds



Security starts outside



Barricade

TECHNICAL SPECIFICATIONS

| Barricade type | 100 | 125 | 150 | 180 | 200 | 250 |
|-----------------------------|------------|------------|------------|------------|------------|------------|
| Height | 1000 | 1250 | 1500 | 1800 | 2000 | 2500 |
| Posts | | | | | | |
| Post | 60 x 60 | 60 x 60 | 60 x 60 | 60 x 60 | 60 x 60 | 60 x 60 |
| Driving depth | 900 | 900 | 900 | 900 | 900 | 900 |
| Bar panel | | | | | | |
| Bars | round 22 | round 22 | round 22 | round 25 | round 25 | round 30 |
| Dragon tail | no | no | yes | yes | yes | yes |
| Upper- & lower beam | 50 x 25 | 50 x 25 | 50 x 25 | 50 x 25 | 50 x 25 | 50 x 25 |
| Bank panel | | | | | | |
| Straight 90 degrees | - | - | yes | yes | yes | yes |
| Sloping 60 degrees | - | - | yes | yes | yes | yes |
| Width | - | - | 1000 | 1000 | 1000 | 1000 |
| Dragon tail around panel | - | - | yes | yes | yes | yes |
| Slope panel (option) | yes | yes | yes | yes | yes | yes |

Dimensions in ca. mm.

Version

Bar panel

- beams: steel hollow section
- bars: round, centre-to-centre distance: 150 mm
- with dragon tail from a 1500 mm height or up: 35 mm sharp points

Posts

- square hollow section
- finish: black plastic cover

Surface treatment

- galvanized
- galvanized, then powder coated according to the Duplex-system

Standard colours

- RAL 6009 (pine green)
 - RAL 6005 (moss green)
 - RAL 9005 (black)
- Other RAL-colours are available upon request.

Options

- shield

Anti-climb protection

- barbed wire (2 or 3 rows)
- razor blade tape (2 or 3 rows)
- rotating pointed segment (1 row, approx. 60 mm or 120 mm)
- rotating pointed combs (single or double row)
- current-carrying detection

Assembly

Posts

- standard: driving depth of approx. 900 mm
- centre-to-centre distance: 2315 mm
- in case of insufficiently compacted soil: assembly of a profiled anchor plate on the sunken part of the post
- in case of a concrete floor: assembly with welded base plates

Bar panels

- blind connection with posts by means of plastic plugs and M8 end-to-end connections

Cope with height differences by:

- slope panels (top beams run parallel to the slope)
- assembly in a cascading way (top beams run horizontally)

B&G Fencing

Industrieweg 187a
NL- 5683 CC Best
PO Box 66
NL-5680 AB Best

Tel.: +31 499 363 666
Fax: +31 499 399 945
info@bgfencing.com

B&G Belgique

Wayenborgstraat 11
2800 Mechelen

Tel.: (015) 202 400
Fax: (015) 206 200
info@bgcloture.be



www.bgfencing.com

